



VHX-71C-CAP

Dakota Digital VHX Instrument Installation
For 1971-'76 Chevrolet Caprice/Impala

Your new VHX-71C-CAP kit includes:

VHX Display



Universal Sender Pack




Switch Assembly



36" CAT5 Cable

(3) Black 1.5" Screws



Control Box

Installation


1. First, remove the lower gauge cover from the dash. Retain the factory hardware for reassembly.



2. Remove the gear selector and retain the hardware. Also remove the clear lens housing.




3. Remove the stock gauges, bulbs, and speedometer cable clamp. Set these items aside; they will not be reused.



4. A few stock mounting areas needed to be trimmed flush to the housing to allow the VHX system to mount properly; they are noted below with white arrows.



5. Attach the provided CAT5 cable to the back of the VHX system and carefully route the open end of the CAT5 cable through the stock speedometer cable opening and to the control box mounting location.



6. Mount the VHX system to the stock housing using the three (3) supplied black screws in the stock mounting locations and re-install the gear selector using the stock hardware.



7. Re-install the lower gauge cover using the factory hardware and refer to the main manual for wiring instructions to complete the VHX installation.



⚠️WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



4510 W. 61st St. North
Sioux Falls, SD 57107
www.dakotadigital.com
dakotasupport@dakotadigital.com

Phone (605) 332-6513
Fax (605) 339-4106

Copyright 2011 - Dakota Digital, Inc.