



WWW.DAKOTADIGITAL.COM

VHX-90F-MUS

Dakota Digital VHX Instrument Installation
For 1990-'93 Ford Mustang

Your new VHX-90F-MUS kit includes:

VHX Display



Universal Sender Pack



Switch Assembly

Installation Manuals



(1) 36" CAT5 Cable

Ford Speed
Sensor Plug



Control Box



Alternator Load Harness

Manual # 650475C

Installation

1. Remove the stock gauge bezel from the dash and save all hardware for reassembly.



2. Remove the stock gauge cluster by removing the four screws holding the system to the dash structure; be sure to keep these screws as they will be re-used. Now is a good time to clean the bezel and dash pads.



3. Connect the CAT5 cable to the back of the VHX cluster as it is installed into the dash, take care when routing the other end of this cable to the control box mounting location. Mount the VHX cluster to the dash structure using the four factory screws.



4. Refer to the main manual for wiring instructions to complete the VHX installation.



5. Stock Mustang charging systems will need an additional wiring connection at the gauge cluster connector. You will need to add a 300 to 500 ohm resistor between pin 14 (LG/R wire) and Pin 2 (R/LG wire). The provided alternator load harness can be used to achieve this.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



4510 W. 61st St. North
Sioux Falls, SD 57107
www.dakotadigital.com
dakotasupport@dakotadigital.com Phone (605) 332-6513
Fax (605) 339-4106 Copyright 2011 - Dakota Digital, Inc.